

American Wire and Cable

Phone 440 235-1140 Fax 440 235-3330

UL Style	CSA	AWG	STND **	MIL	TEMP	Voltage	Nominal OD
EPDM Appliance Wiring Material (AWM) - 125 C							
3484	AWM	8	165/30	45 Mil	125C	600	0.265
3484	AWM	10	105/30	30 Mil	125 C	600	0.189
3484	AWM	12	65/30	30 Mil	125 C	600	0.156
3484	AWM	14	41/30	30 Mil	125 C	600	0.133
3484	AWM	16	26/30	30 Mil	125 C	600	0.117
3484	AWM	18	16/30	30 Mil	125 C	600	0.107
3484	AWM	20	10/30	30 Mil	125 C	600	0.102
3284	AWM	6	133/st	60 Mil	125C	600	0.336
3284	AWM	8	165/30	60 Mil	125C	600	0.297
3284	AWM	10	105/30	45 Mil	125C	600	0.222
3284	AWM	12	65/30	45 Mil	125C	600	0.183
3284	AWM	14	41/30	45 Mil	125C	600	0.163
3284	AWM	16	26/30	45 Mil	125C	600	0.145
3284	AWM	18	16/30	45 Mil	125C	600	0.140
3284	AWM	20	10/30	45 Mil	125C	600	0.131
3328	AWM	16	26/30	60 Mil	125 C	600	0.180
3328	AWM	18	16/30	60 Mil	125 C	600	0.169
3330	AWM	10	105/30	80 Mil	125 C	600	0.281
3330	AWM	12	65/30	80 Mil	125 C	600	0.248
3330	AWM	14	41/30	80 Mil	125 C	600	0.228

Put-ups: Drums (20", 30", or 42"), Reels, or Plastic Spools

** Other possible stranding: Solid, 7/St, 19/St, 49/St, or 133/St - Bare or Tinned

12/20/2012