

American Wire and Cable

Phone 440 235-1140 Fax 440 235-3330

UL Style	CSA	AWG	STND**	MIL	TEMP	Voltage	Nominal OD
Silicone Rubber AWM Wire - 200 C							
3135	AWM	12	19/ST	30 Mil	200	600	0.151
3135	AWM	14	7/ST	30 Mil	200	600	0.132
3135	AWM	16	7/ST	30 Mil	200	600	0.117
3135	AWM	18	7/ST	30 Mil	200	600	0.107
3139	AWM	12	19/ST	45 Mil	200	600	0.181
3139	AWM	14	7/ST	45 Mil	200	600	0.162
3139	AWM	16	7/ST	45 Mil	200	600	0.144
3139	AWM	18	7/ST	45 Mil	200	600	0.140
3143	AWM	12	19/ST	60 Mil	200	600	0.214
3143	AWM	14	7/ST	60 Mil	200	600	0.195
3143	AWM	16	7/ST	60 Mil	200	600	0.179
3143	AWM	18	7/ST	60 Mil	200	600	0.169
Silicone Rubber AWM Wire - 150 C							
3134	AWM	12	65/30	30 Mil	150	600	0.153
3134	AWM	14	41/30	30 Mil	150	600	0.133
3134	AWM	16	26/30	30 Mil	150	600	0.117
3134	AWM	18	16/30	30 Mil	150	600	0.107
3138	AWM	12	65/30	45 Mil	150	600	0.183
3138	AWM	14	41/30	45 Mil	150	600	0.163
3138	AWM	16	26/30	45 Mil	150	600	0.145
3138	AWM	18	16/30	45 Mil	150	600	0.140
3142	AWM	12	65/30	60 Mil	150	600	0.217
3142	AWM	14	41/30	60 Mil	150	600	0.195
3142	AWM	16	26/30	60 Mil	150	600	0.180
3142	AWM	18	16/30	60 Mil	150	600	0.169
Put-ups: Reels or Plastic Spools							
** Other possible stranding: Solid - All stranding is Tinned							

#####